



SAW Components

Data Sheet B4232





SAW Components

B4232

Low-Loss '2 in 1' Filter for Mobile Communication

769,0/860,5 MHz

Data Sheet


Features

- Low-loss '2 in 1' RF filter for Trunked Radio
- Device with two integrated Rx filters
- Low amplitude ripple
- Usable passband filter 1: 19,0 MHz
- Usable passband filter 2: 14,0 MHz
- No matching network required for operation at 50 Ω
- Package for **Surface Mounted Technology (SMT)**

Terminals

- Ni, gold-plated


Ceramic package QCC8E



Dimensions in mm, approx. weight 0,027g

Pin configuration

- | | |
|-----|-------------------|
| 1 | Input (filter 1) |
| 7 | Output (filter 1) |
| 3 | Input (filter 2) |
| 5 | Output (filter 2) |
| 2,6 | Ground |
| 4,8 | Case ground |



Type	Ordering code	Marking and Package according to	Packing according to
B4232	B39861-B4232-H410	C61157-A7-A92	F61074-V8174-Z000

Electrostatic Sensitive Device (ESD)

Maximum ratings

Operable temperature range	T	- 40 / + 85	°C	Machine Model, 10 pulses source and load impedance 50 Ω
Storage temperature range	T_{stg}	- 40 / + 85	°C	
DC voltage	V_{DC}	5	V	
ESD voltage	V_{ESD}^*	100	V	
Source power (cw)	P_S	15	dBm	

*-acc. to JESD22-A115A (Machine Model), 10 negative & 10 positive pulses



Data Sheet

Characteristics filter 1

Operating temperature range: $T = 25 \pm 2 \text{ }^\circ\text{C}$
 Terminating source impedance: $Z_S = 50 \text{ }\Omega$
 Terminating load impedance: $Z_L = 50 \text{ }\Omega$

		min.	typ.	max.	
Nominal frequency	f_N	—	860,5	—	MHz
Maximum insertion attenuation	α_{max}				
	851,0 ... 870,0 MHz	—	2,1	2,5	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
	851,0 ... 870,0 MHz	—	0,7	1,1	dB
Group delay ripple (p-p)	$\Delta\tau$				
	851,0 ... 870,0 MHz	—	20,0	50,0	ns
Return loss (Input and Output)					
	851,0 ... 870,0 MHz	10,0	11,5	—	dB
Absolute attenuation	α_{abs}				
	0,1 ... 483,0 MHz	57	60	—	dB
	483,0 ... 676,0 MHz	50	60	—	dB
	676,0 ... 724,0 MHz	40	64	—	dB
	741,4 ... 773,0 MHz	30	59	—	dB
	804,0 ... 822,0 MHz	20	42	—	dB
	880,0 MHz	7	11	—	dB
	898,0 ... 918,0 MHz	20	40	—	dB
	946,0 ... 967,0 MHz	30	59	—	dB
	1040,0 ... 1070,0 MHz	46	54	—	dB
	1070,0 ... 1256,0 MHz	43	50	—	dB
	1256,0 ... 2000,0 MHz	30	40	—	dB
Temperature coefficient of frequency	TC_f	—	- 36	—	ppm/K



Data Sheet

Characteristics filter 1


Operating temperature range: $T = -30 \dots +70 \text{ }^\circ\text{C}$
 Terminating source impedance: $Z_S = 50 \text{ }\Omega$
 Terminating load impedance: $Z_L = 50 \text{ }\Omega$

		min.	typ.	max.	
Nominal frequency	f_N	—	860,5	—	MHz
Maximum insertion attenuation	α_{\max}				
	851,0 ... 870,0 MHz	—	2,4	2,7	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
	851,0 ... 870,0 MHz	—	1,0	1,3	dB
Group delay ripple (p-p)	$\Delta\tau$				
	851,0 ... 870,0 MHz	—	30,0	50,0	ns
Return loss (Input and Output)					
	851,0 ... 870,0 MHz	10,0	11,0	—	dB
Absolute attenuation	α_{abs}				
	0,1 ... 483,0 MHz	57	60	—	dB
	483,0 ... 676,0 MHz	50	60	—	dB
	676,0 ... 724,0 MHz	40	64	—	dB
	741,4 ... 773,0 MHz	30	59	—	dB
	804,0 ... 822,0 MHz	20	42	—	dB
	880,0 MHz	4	7	—	dB
	898,0 ... 918,0 MHz	20	38	—	dB
	946,0 ... 967,0 MHz	30	59	—	dB
	1040,0 ... 1070,0 MHz	46	54	—	dB
	1070,0 ... 1256,0 MHz	43	50	—	dB
	1256,0 ... 2000,0 MHz	30	40	—	dB
Temperature coefficient of frequency	TC_f	—	- 36	—	ppm/K




Data Sheet

Transfer function filter 1 (narrow band)



Transfer function filter 1 (wide band)





Data Sheet

Characteristics filter 2

Operating temperature range: $T = 25 \pm 2 \text{ }^\circ\text{C}$
 Terminating source impedance: $Z_S = 50 \text{ }\Omega$
 Terminating load impedance: $Z_L = 50 \text{ }\Omega$

		min.	typ.	max.	
Nominal frequency	f_N	—	769,0	—	MHz
Maximum insertion attenuation	α_{max}				
	762,0 ... 776,0 MHz	—	1,7	2,4	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
	762,0 ... 776,0 MHz	—	0,4	1,0	dB
Group delay ripple (p-p)	$\Delta\tau$				
	762,0 ... 776,0 MHz	—	22,0	50,0	ns
Return loss (Input and Output)					
	762,0 ... 776,0 MHz	12,0	13,0	—	dB
Absolute attenuation	α_{abs}				
	0,0 ... 431,0 MHz	57	60	—	dB
	431,0 ... 604,0 MHz	50	60	—	dB
	604,0 ... 690,0 MHz	30	62	—	dB
	690,0 ... 733,0 MHz	20	56	—	dB
	733,0 ... 752,0 MHz	9	18	—	dB
	804,0 ... 847,0 MHz	25	36	—	dB
	847,0 ... 892,7 MHz	30	54	—	dB
	892,7 ... 910,7 MHz	50	56	—	dB
	910,7 ... 995,3 MHz	47	54	—	dB
	995,3 ... 1121,0 MHz	42	52	—	dB
Temperature coefficient of frequency	TC_f	—	- 36	—	ppm/K



SAW Components

B4232

Low-Loss '2 in 1' Filter for Mobile Communication

769,0/860,5 MHz

Data Sheet

Characteristics filter 2


Operating temperature range: $T = -30 \dots +70 \text{ }^\circ\text{C}$
 Terminating source impedance: $Z_S = 50 \text{ } \Omega$
 Terminating load impedance: $Z_L = 50 \text{ } \Omega$

		min.	typ.	max.	
Nominal frequency	f_N	—	769,0	—	MHz
Maximum insertion attenuation	α_{\max}				
	762,0 ... 776,0 MHz	—	1,8	2,6	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
	762,0 ... 776,0 MHz	—	0,5	1,0	dB
Group delay ripple (p-p)	$\Delta\tau$				
	762,0 ... 776,0 MHz	—	30,0	50,0	ns
Return loss (Input and Output)					
	762,0 ... 776,0 MHz	12,0	13,0	—	dB
Absolute attenuation	α_{abs}				
	0,0 ... 431,0 MHz	57	60	—	dB
	431,0 ... 604,0 MHz	50	60	—	dB
	604,0 ... 690,0 MHz	30	62	—	dB
	690,0 ... 733,0 MHz	20	56	—	dB
	733,0 ... 752,0 MHz	9	16	—	dB
	804,0 ... 847,0 MHz	25	34	—	dB
	847,0 ... 892,7 MHz	30	54	—	dB
	892,7 ... 910,7 MHz	50	56	—	dB
	910,7 ... 995,3 MHz	47	54	—	dB
	995,3 ... 1121,0 MHz	42	52	—	dB
Temperature coefficient of frequency	TC_f	—	- 36	—	ppm/K




Data Sheet

Transfer function filter 2 (narrow band)



Transfer function filter 2 (wide band)





SAW Components

B4232

Low-Loss '2 in 1' Filter for Mobile Communication

769,0/860,5 MHz

Data Sheet

Published by EPCOS AG

Surface Acoustic Wave Components Division, SAW MC PD

P.O. Box 80 17 09, D-81617 München

© EPCOS AG 2004. All Rights Reserved. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

The information contained in this brochure describes the type of component and shall not be considered as guaranteed characteristics. Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.