



SAW multimedia filters

Series/Type: M3953M

The following products presented in this data sheet are being withdrawn.

Ordering Code	Substitute Product	Date of Withdrawal	Deadline Last Orders	Last Shipments
B39458M3953M100		2011-01-14	2011-09-30	2012-09-30

For further information please contact your nearest EPCOS sales office, which will also support you in selecting a suitable substitute. The addresses of our worldwide sales network are presented at www.epcos.com/sales.



SAW Components

M 3953 M

SAW IF filter

45.75 MHz

Data Sheet


Application

- Standard: M/N
- TV IF filter with Nyquist slope and sound suppression
- High color carrier level
- Constant group delay




Features

- Plastic package **SIP5K**
- Approximate weight 1.0 g
- RoHS compatible
- Tinned CuFe alloy terminals



Pin configuration

- 1 Input
- 2 Input - ground
- 2 Chip carrier - ground
- 3 Output
- 4 Output



Please read *cautions and warnings and important notes* at the end of this document.


SAW Components
M 3953 M
SAW IF filter
45.75 MHz
Data Sheet
Characteristics

Reference temperature: $T_A = 25 (45) \text{ }^\circ\text{C}$
 Terminating source impedance: $Z_S = 50 \text{ } \Omega$
 Terminating load impedance: $Z_L = 2 \text{ k}\Omega \parallel 3 \text{ pF}$

		min.	typ. @ 25 °C	max.	
Insertion attenuation	α				
Reference level for the following data	44.06 (44.00) MHz	11.2	12.7	14.2	dB
Relative attenuation	α_{rel}				
Picture carrier	45.81 (45.75) MHz	5.2	6.2	7.2	dB
Color carrier	42.23 (42.17) MHz	-0.5	0.2	0.9	dB
	41.98 (41.92) MHz	0.2	0.9	1.6	dB
Sound carrier	41.31 (41.25) MHz	25.0	37.0	—	dB
Adj. picture carrier	39.81 (39.75) MHz	48.0	63.0	—	dB
Adj. sound carrier	47.31 (47.25) MHz	46.0	57.0	—	dB
Lower sidelobe	35.06 ... 39.81 (35.00 ... 39.75) MHz	40.0	45.0	—	dB
Upper sidelobe	47.31 ... 55.06 (47.25 ... 55.00) MHz	37.0	43.0	—	dB
Reflected wave signal suppression					
1.3 μs ... 6.0 μs after main pulse (test pulse 250 ns, carrier frequency 44.06 MHz)		42.0	52.0	—	dB
Feedthrough signal suppression					
1.3 μs ... 1.2 μs before main pulse (test pulse 250 ns, carrier frequency 44.06 MHz)		50.0	56.0	—	dB
Group delay ripple (p-p)	$\Delta\tau$	—	40	—	ns
Impedance at 44.06 MHz					
Input: $Z_{IN} = R_{IN} \parallel C_{IN}$		—	1.1 \parallel 15.6	—	k Ω \parallel pF
Output: $Z_{OUT} = R_{OUT} \parallel C_{OUT}$		—	1.0 \parallel 4.0	—	k Ω \parallel pF
Temperature coefficient of frequency	TC_f	—	-72	—	ppm/K



SAW Components

M 3953 M

SAW IF filter

45.75 MHz

Data Sheet

Maximum ratings

Operable temperature range	T	-25 / +65	°C	
Storage temperature range	T _{stg}	-40 / +85	°C	
DC voltage	V _{DC}	5	V	
AC voltage	V _{pp}	10	V	between any terminals



SAW Components



M 3953 M

SAW IF filter

45.75 MHz

Data Sheet

Frequency response



Please read *cautions and warnings* and *important notes* at the end of this document.



SAW Components


M 3953 M

SAW IF filter


45.75 MHz

Data Sheet

Frequency response



Time domain response



Please read *cautions and warnings* and *important notes* at the end of this document.



SAW Components	M 3953 M
SAW IF filter	45.75 MHz

Data Sheet

References

Type	M 3953 M
Ordering code	B39458-M3953-M100
Marking and package	C61157-A1-A15
Packaging	F61074-V8067-Z000
Date codes	L_1126
S-parameters	
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG
Surface Acoustic Wave Components Division
P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2009. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSSP, CTVS, DSSP, MiniBlue, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseMod, SIFERRIT, SIFI, SIKOREL, SilverCap, SIM-DAD, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.