



Inductors

March 2010

## SMD pulse transformers for LAN applications

TDK-EPC, a group company of TDK Corporation, has developed a series of TDK pulse transformers in SMD design for LAN use. The new product enables customers to employ automated placement of all components on the circuit board and using reflow solder and thus simplify their manufacturing processes. With an inductance of at least 200  $\mu\text{H}$  and an insertion loss of not more than 1.5 dB, the new ALT4532-001T series of

pulse transformers features the similar electrical properties as its predecessor product. Mass production began in February 2010.

The new design was made possible by the use of advanced fully automated wire winding and packaging that replaces the former manual processes. After winding, the wires to the contact pads are also attached automatically and the package is finished using thermo-compression bonding. The result is higher quality and reliability.

The benefits of the product's SMD design come into full play when the pulse transformer is used in combination with a common-mode filter to eliminate differential noise. Together, their mounting area is about 35 percent smaller because the previous version required that the two kinds of components be combined into a module with its own packaging.

The new component is used for the transmission of differential pulse signals in high-speed LANs such as 100BASE-TX. The ALT4532-001T series of pulse transformers is expected to be used mainly in digital consumer electronic applications that offer LAN connectivity such as game consoles and Internet radios as well as in PCs.

### Glossary

- SMD: Surface mounted devices are electronic components that feature contact pads rather than pins and can be mounted on the surface of a printed circuit board using fully automated pick and place systems and reflow soldering techniques.
- 100BASE-TX: this LAN standard uses one pair of twisted wires in each direction, providing a transmission rate of 100 Mbit/s each direction.

### Main applications

- Digital consumer electronics applications with LAN connectivity such as game consoles or Internet radios as well as in PCs

### Main features and benefits

- The SMD component enables customers to simplify their manufacturing processes by using auto-mated placement of all components on the circuit board and reflow soldering processes.

### Key data

<b>Inductance</b>	$\geq 200 \mu\text{H}$
<b>Insertion loss</b>	$\leq 1.5 \text{ dB}$
<b>Line capacitance</b>	$\leq 35 \text{ pF}$
<b>Isolation voltage</b>	1500 V AC/1 min.
<b>Operating temperature range</b>	0 °C to +70 °C
<b>Dimensions</b>	4.5 × 3.2 × 2.8 mm <sup>3</sup>

# COMPONENTS

The Customer Magazine of TDK-EPC Corporation



Products & Technologies

---