



Film Capacitors

Weights

Date: May 2009

Weights

The following table contains the weights for all **radial-lead capacitors (2 pins) with plastic casings**.

Deviations of up to approximately $\pm 30\%$ are possible.

| Lead spacing/ Type number | Dimensions w × h × l mm | Weight g | Lead spacing/ Type number | Dimensions w × h × l mm | Weight g |
|------------------------------|-------------------------------|-------------|------------------------------|-------------------------------|-------------|
| Lead spacing 5 mm | | | Lead spacing 22.5 mm | | |
| B32529, | 2.5 × 6.5 × 7.2 | 0.20 | B32023, B32523, | 6.0 × 15.0 × 26.5 | 4.0 |
| B32559 | 3.0 × 6.5 × 7.2 | 0.25 | B32573, B32593, | 7.0 × 16.0 × 26.5 | 4.8 |
| | 3.5 × 8.0 × 7.2 | 0.32 | B32613, B32633, | 7.5 × 14.0 × 26.5 | 4.7 |
| | 4.5 × 9.5 × 7.3 | 0.46 | B32653, B32673, | 8.5 × 16.5 × 26.5 | 5.5 |
| | 5.0 × 10.0 × 7.5 | 0.54 | B32913, B32923, | 9.0 × 14.0 × 26.5 | 5.6 |
| | 6.0 × 10.5 × 7.5 | 0.68 | B81123 | 10.5 × 16.5 × 26.5 | 7.5 |
| | 7.8 × 13.0 × 7.8 | 0.90 | | 10.5 × 18.5 × 26.5 | 8.0 |
| Lead spacing 7.5 mm | | | | 10.5 × 20.5 × 26.5 | 8.5 |
| B32520, | 2.5 × 7.0 × 10.0 | 0.30 | | 11.0 × 20.5 × 26.5 | 9.0 |
| B32620 | 3.0 × 8.0 × 10.0 | 0.40 | | 12.0 × 22.0 × 26.5 | 10.5 |
| | 4.0 × 8.5 × 10.0 | 0.52 | | 14.5 × 29.5 × 26.5 | 18.9 |
| | 5.0 × 10.5 × 10.0 | 0.80 | Lead spacing 27.5 mm | | |
| | 6.0 × 12.0 × 10.3 | 0.98 | B32024 | 11.0 × 19.0 × 31.5 | 9.5 |
| Lead spacing 10 mm | | | B32524, B32594, | 11.0 × 21.0 × 31.5 | 10 |
| B32021, B32521, | 4.0 × 7.0 × 13.0 | 0.52 | B32614, B32634, | 12.5 × 21.5 × 31.5 | 13 |
| B32591, B32601, | 4.0 × 9.0 × 13.0 | 0.70 | B32654, B32674, | 13.5 × 23.0 × 31.5 | 15 |
| B32621, B32651, | 5.0 × 11.0 × 13.0 | 1.1 | B32774, | 14.0 × 24.5 × 31.5 | 16 |
| B32671, | 6.0 × 12.0 × 13.0 | 1.4 | B32914, B32924 | 15.0 × 24.5 × 31.5 | 16 |
| B32911, B32921 | | | | 16.0 × 32.0 × 31.5 | 21 |
| Lead spacing 15 mm | | | | 18.0 × 27.5 × 31.5 | 20 |
| B32022, B32522, | 5.0 × 10.5 × 18.0 | 1.5 | | 18.0 × 33.0 × 31.5 | 24.5 |
| B32572, B32592, | 6.0 × 11.0 × 18.0 | 1.9 | | 19.0 × 30.0 × 31.5 | 23 |
| B32602, | 6.0 × 12.0 × 18.0 | 2.1 | | 21.0 × 31.0 × 31.5 | 26.3 |
| B32612, B32632, | 7.0 × 12.5 × 18.0 | 2.5 | | 22.0 × 36.5 × 31.5 | 33 |
| B32652, B32672, | 8.0 × 14.0 × 18.0 | 3.2 | Lead spacing 37.5 mm | | |
| B32912, B32922, | 8.5 × 14.5 × 18.0 | 3.3 | B32026, B32526, | 12.0 × 22.0 × 42.0 | 18 |
| B81123 | 9.0 × 17.5 × 18.0 | 4.5 | B32656, B32676 | 14.0 × 25.0 × 42.0 | 20 |
| | 11.0 × 18.5 × 18.0 | 5.6 | B32686A, | 16.0 × 28.5 × 42.0 | 25 |
| | 13.0 × 14.0 × 18.0 | 4.1 | B32776, | 18.0 × 32.5 × 41.5 | 32 |
| | | | B32916, B32926 | 20.0 × 39.5 × 41.5 | 40 |
| | | | | 20.0 × 39.5 × 42.0 | 40 |
| | | | | 28.0 × 42.5 × 41.5 | 60 |
| Lead spacing 52.5 mm | | | Lead spacing 52.5 mm | | |
| | | | B32678, B32778 | 30.0 × 45.0 × 57.5 | 90 |
| | | | B32928 | 35.0 × 50.0 × 57.5 | 120 |

Weights

SilverCap™

| Lead spacing/ Type number | Dimensions w × h × l mm | Weight g |
|------------------------------|-------------------------------|-------------|
| Lead spacing 7.5 mm | | |
| B32560 | 9.8 × 11.0 × 9.0 | 0.98 |
| Lead spacing 10 mm | | |
| B32561 | 8.8 × 13.3 × 11.0 | 1.45 |
| Lead spacing 15 mm | | |
| B32562, B32572 | 13.9 × 14.5 × 16.5 | 3.90 |

| Lead spacing/ Type number | Dimensions w × h × l mm | Weight g |
|------------------------------|-------------------------------|-------------|
| Lead spacing 22.5 mm | | |
| B32563, B32573 | 12.8 × 17.2 × 24.0 | 6.67 |
| Lead spacing 27.5 mm | | |
| B32564 | 16.0 × 20.0 × 29.0 | 11.24 |